# address (Address)

b2bOpticInfo → header → orderParties → address

| addressLine | |
|---|---|
| **type** | string |
| **occurs** | 0..3 |
| **description** | street name with house number or building (part of postal address) |
| **poBox** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | postbox |
| **province** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | province |
| **region** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | region |
| **state** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | state |
| **city** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | city |
| **zip** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | zip code of postal company |
| **countryCode** | |
| **type** | string |
| **occurs** | 0..1 |
| **description** | country code in ISO-3166-2 |

```
<xs:complexType name="Address">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="3" name="addressLine"
type="xs:string" />
    <xs:element minOccurs="0" name="poBox" type="xs:string" />
    <xs:choice minOccurs="0">
      <xs:element name="province" type="xs:string" />
      <xs:element name="region" type="xs:string" />
      <xs:element name="state" type="xs:string" />
```

```
    </xs:choice>
    <xs:element name="city" type="xs:string" />
    <xs:element name="zip" type="xs:string" />
    <xs:element name="countryCode" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

From:
http://wiki.b2boptic.com/ - **wiki.b2bOptic.com**

Permanent link:
**http://wiki.b2boptic.com/en:lensinfo:version000300:complextypes:address**

Last update: **2013/06/05 14:27**