

# XML-Structure

## Root-Element: b2bOpticInfo

In the root-element the location of the XSD at schema.b2boptic.com is mandatory, so the receiver could identify the version of XML.

```
<b2bOpticInfo xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="http://schema.b2boptic.com/b2boptic_lensinfo_
1.0.0.xsd">
```

<b>items</b>	
<b>type</b>	sequence of item
<b>occurs</b>	1
<b>description</b>	main tag that include a list of status info items
<b>item (element of items)</b>	
<b>type</b>	B2BInfoItem
<b>occurs</b>	1..n
<b>description</b>	a status info for one order
<b>experimental</b>	
<b>type</b>	anyType
<b>occurs</b>	0..n
<b>description</b>	section for internal tests at development

```
<xs:element name="b2bOpticInfo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="items">
        <xs:complexType>
          <xs:sequence>
            <xs:element maxOccurs="unbounded" name="item"
type="B2BInfoItem" />
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="experimental"
type="xs:anyType" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

From:

<https://wiki.b2boptic.com/> - **wiki.b2bOptic.com**



Permanent link:

<https://wiki.b2boptic.com/en:lensinfo:version010000:structure>

Last update: **2014/01/03 15:24**