
XML-Structure

Root-Element: b2boptic



In the root-element the location of the XSD at schema.b2boptic.com should be set, so the receiver could identify the version of XML. In next version it will be mandatory.

```
<b2bOptic xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="http://schema.b2boptic.com/b2boptic_v1.6.2.xsd">
```

header	
type	Header
occurs	1
description	head section with information about all orders in this xml
items	
type	sequence of item
occurs	1
description	main tag that include a list of order items
item (element of items)	
type	Item
occurs	1..n
description	one order
experimental	
type	anyType
occurs	0..n
description	section for internal tests at development

```
  <xs:element name="b2bOptic">
    <xs:complexType>
      <xs:sequence>
    <xs:element name="header" type="Header"/>
    <xs:element name="items">
      <xs:complexType>
        <xs:sequence>
              <xs:element name="item" type="Item" maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
```

```
        </xs:element>
        <xs:element name="experimental" type="xs:anyType" minOccurs="0"
maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
```

From:
http://wiki.b2boptic.com/ - **wiki.b2bOptic.com**

Permanent link:
http://wiki.b2boptic.com/en:lensorder:version010602:structure

Last update: **2016/05/09 06:24**