

# DownloadOrderFromPlatform

## request

<b>manufacturer</b>	
<b>type</b>	string
<b>occurs</b>	0..1
<b>description</b>	the supplier code (see <a href="#">company list</a> )
<b>customerid</b>	
<b>type</b>	string
<b>occurs</b>	1
<b>description</b>	the username that was given to the customer to access this webservice; usually this is the customer number
<b>username</b>	
<b>type</b>	string
<b>occurs</b>	0..1
<b>description</b>	the username that was given to the customer to access this webservice; this is only used if a username and a customer number needs to be transmitted
<b>password</b>	
<b>type</b>	string
<b>occurs</b>	1
<b>description</b>	the password that was given to the customer to access this webservice; this is transferred in plaintext
<b>referenceNo</b>	
<b>type</b>	string
<b>occurs</b>	1
<b>description</b>	the value of <a href="#">referenceNo</a> (b2boptic → items → item) of the order that was send by the client with <a href="#">UploadOrderToPlatform</a>

```

<xsd:element name="DownloadOrderFromPlatform">
  <xsd:complexType>
    <xsd:complexContent>
      <xsd:extension base="b2b:Ws_AuthenticationType">
        <xsd:sequence>
          <xsd:element name="referenceNo" type="xsd:string" />
        </xsd:sequence>
      </xsd:extension>
    </xsd:complexContent>
  </xsd:complexType>
</xsd:element>
<xsd:complexType name="Ws_AuthenticationType">
  <xsd:sequence>
    <xsd:element name="manufacturer" type="xsd:string" minOccurs="0" />
    <xsd:element name="customerid" type="xsd:string" />
    <xsd:element name="username" type="xsd:string" minOccurs="0" />
    <xsd:element name="password" type="xsd:string" />
  </xsd:sequence>

```

```
</xsd:complexType>
```

## response

<b>b2bxmlorder (part of choice)</b>	
<b>type</b>	string
<b>occurs</b>	1
<b>description</b>	the order in <a href="#">B2BOptic LensOrder 1.6.0</a> format; the xml document is included in a CDATA-section ( <a href="http://www.w3.org/TR/REC-xml/#dt-cdsection">http://www.w3.org/TR/REC-xml/#dt-cdsection</a> )
<b>b2bxmlinfo (part of choice)</b>	
<b>type</b>	string
<b>occurs</b>	1
<b>description</b>	the status info about the order in <a href="#">B2BOptic LensInfo 0.3.0</a> format; the xml document is included in a CDATA-section ( <a href="http://www.w3.org/TR/REC-xml/#dt-cdsection">http://www.w3.org/TR/REC-xml/#dt-cdsection</a> )
<b>errorCode (part of choice)</b>	
<b>type</b>	int
<b>occurs</b>	1
<b>description</b>	an error code from server
<b>errorText (part of choice)</b>	
<b>type</b>	string
<b>occurs</b>	1
<b>description</b>	a description for the error by the server
<b>errorTextUser (part of choice)</b>	
<b>type</b>	string
<b>occurs</b>	0..1
<b>description</b>	a error description text in native language of the user, that the client can display

```
<xsd:element name="DownloadOrderFromPlatformResponse">
  <xsd:complexType>
    <xsd:choice>
      <xsd:sequence>
        <xsd:element name="b2bxmlorder" type="xsd:string" />
        <xsd:element name="b2bxmlinfo" type="xsd:string" />
      </xsd:sequence>
      <xsd:sequence>
        <xsd:element name="errorCode" type="xsd:int" />
        <xsd:element name="errorText" type="xsd:string" />
        <xsd:element name="errorTextUser" type="xsd:string" minOccurs="0" />
      </xsd:sequence>
    </xsd:choice>
  </xsd:complexType>
</xsd:element>
```

From:  
<https://wiki.b2boptic.com/> - **wiki.b2bOptic.com**

Permanent link:  
<https://wiki.b2boptic.com/en:webservice:version010000:structure:downloadorderfromplatform>

Last update: **2013/06/05 10:12**

