

UploadOrderToPlatform

request

| | |
|---------------------|---|
| manufacturer | |
| type | string |
| occurs | 0..1 |
| description | the supplier code (see company list) |
| customerid | |
| type | string |
| occurs | 1 |
| description | the username that was given to the customer to access this webservice; usually this is the customer number |
| username | |
| type | string |
| occurs | 0..1 |
| description | the username that was given to the customer to access this webservice; this is only used if a username and a customer number needs to be transmitted |
| password | |
| type | string |
| occurs | 1 |
| description | the password that was given to the customer to access this webservice; this is transferred in plaintext |
| b2bxmlorder | |
| type | string |
| occurs | 1 |
| description | the order in B2BOptic LensOrder 1.6.0 format; the xml document is included in a CDATA-section (http://www.w3.org/TR/REC-xml/#dt-cdsection) |
| orderstatus | |
| type | Ws_OrderStatusType |
| occurs | 1 |
| description | status of the order in sender program |

```
<xsd:element name="UploadOrderToPlatform">
  <xsd:complexType>
    <xsd:complexContent>
      <xsd:extension base="b2b:Ws_AuthenticationType">
        <xsd:sequence>
          <xsd:element name="b2bxmlorder" type="xsd:string" />
          <xsd:element name="orderstatus" type="b2b:Ws_OrderStatusType" />
        </xsd:sequence>
      </xsd:extension>
    </xsd:complexContent>
  </xsd:complexType>
</xsd:element>
<xsd:complexType name="Ws_AuthenticationType">
```

```
<xsd:sequence>
  <xsd:element name="manufacturer" type="xsd:string" minOccurs="0" />
  <xsd:element name="customerid" type="xsd:string" />
  <xsd:element name="username" type="xsd:string" minOccurs="0" />
  <xsd:element name="password" type="xsd:string" />
</xsd:sequence>
</xsd:complexType>
```

response

| | |
|---------------------------------------|--|
| url (part of choice) | |
| type | string |
| occurs | 1 |
| description | the URL to the web platform that is launched by the client in a internet browser and shown to the user. It may include all parameter that are necessary to open the platform with the uploaded order; URL syntax like in RFC3986 (http://www.ietf.org/rfc/rfc3986.txt) |
| errorCode (part of choice) | |
| type | int |
| occurs | 1 |
| description | an error code from server |
| errorText (part of choice) | |
| type | string |
| occurs | 1 |
| description | a description for the error by the server |
| errorTextUser (part of choice) | |
| type | string |
| occurs | 0..1 |
| description | a error description text in native language of the user, that the client can display |

```
<xsd:element name="UploadOrderToPlatformResponse">
  <xsd:complexType>
    <xsd:choice>
      <xsd:sequence>
        <xsd:element name="url" type="xsd:string" />
      </xsd:sequence>
      <xsd:sequence>
        <xsd:element name="errorCode" type="xsd:int" />
        <xsd:element name="errorText" type="xsd:string" />
        <xsd:element name="errorTextUser" type="xsd:string" minOccurs="0" />
      </xsd:sequence>
    </xsd:choice>
  </xsd:complexType>
</xsd:element>
```

From:
<https://wiki.b2boptic.com/> - **wiki.b2bOptic.com**

Permanent link:
<https://wiki.b2boptic.com/en:webservice:version010000:structure:uploadordertoplatform>

Last update: **2013/06/05 10:11**

